# **TEK037 ANTI-STONECHIP WHITE**

## 1. Introduction

A range of high quality rubberised coatings designed to provide body panel protection from physical traffic induced damage.

#### 2. Where to use

Lower body panels including sills and valences.

## 3. Where not to use

This product is a specific rubberised coating, and should be used only for the intended application.

#### 4. Benefits

- Protects against stone chip damage
- Prevents corrosion
- Protection against stone chip damage
- Protection against paint cracking and scratching
- Helps deaden sound and vibration

## 5. Physical properties [Stoneguard base except where stated].

Appearance

pН

Specific Gravity

Viscosity

Non Volatiles % m/m

Active Content % m/m, as supplied

Flammability, as supplied

Composition Data, as supplied

Volatile Organic Content, as supplied

Service Temperatures

**Application Temperatures** 

Black, white or grey viscous liquids.

Not applicable

0.97 - 1.10

5.500 cPs maximum

35 - 45

20 - 30

Extremely flammable, flash point below -20°C

A solution of a styrenated rubber and hydrocarbon

resins in a blend of solvents. Other components include plasticizers, pigments

and extenders, thixotropes and wetting agents, dispersed in a

butane/propane/isobutane based propellant. Compliant with EU Directive 2004/42/CE

Up to 80°C.

10 - 25°C



## 6. Application Details

Ensure surfaces are clean, dry, and free from oils, traffic film, greases, tars etc. Wipe over the surface with TEK038 Universal Degreaser, to remove any tar or asphalt deposits, and allow to dry. Mask the area to prevent over spray. Undertake a small test application on an inconspicuous area prior to use to ensure suitability for use. Shake the can thoroughly for at least two minutes. Repeat shaking at regular intervals during use. Spray from a distance of 20 to 30cm. Thinly applied coats built up at 10-15 minute intervals will achieve the best result. Allow at least 24 hrs between applying final coating and any over-painting that may be required. After use invert can and spray to clear nozzle.

## 7. Availability

500ml aerosol

















