

TEK038 UNIVERSAL DEGREASER

1. Introduction

A fast acting solvent blend designed for degreasing metal and paintwork prior to coating.

2. Where to use

Any metallic substrate, for the removal of newly deposited, aged or oxidised greases, oils, bitumen and tar stains, waxes, silicones etc. This product is also suitable for spot removal use on concretes, and on many plastics and painted surfaces subject to successful assessment on an inconspicuous area.

3. Where not to use

Over asphalt, soft plastics and some painted surfaces.

4. Benefits

- Easy to use spray action
- Fast drying formulation
- Dissolves all conventional automotive oils and greases
- Use on metals, plastics and glass
- Safe on most painted surfaces

5. Physical properties [Degreaser base except where stated].

Appearance	A colourless liquid with a hydrocarbon solvent odour.
pH	Not applicable
Specific Gravity	0.770 – 0.800
Viscosity	Thin free flowing liquid
Non Volatiles % m/m	0%
Active Content % m/m, as supplied	75%
Flammability, as supplied	Extremely flammable, flash point below -20°C.
Composition data, as supplied	A blend of aliphatic solvents and alcohol in a butane/isobutane/propane propellant.
Service temperature	Designed for use at ambient temperatures.



6. Application Details

Shake can thoroughly before use. Spray liberally on the designated area. Allow to remain in contact with the surface for a few moments to penetrate and solublise contamination before wiping over with a clean dry lint free cloth. Brushing or other forms of agitation will assist in effective solubilisation of stubborn deposits. Always dispose of contaminated materials in a sealable metal bin to prevent fire risk.

7. Availability

500ml aerosol