



**SAFETY DATA SHEET  
TEK FADE OUT THINNER 500ML**

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

**1.1. Product identifier**

Product name                      TEK FADE OUT THINNER 500ML  
Product No.                        TEK027

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**1.3. Details of the supplier of the safety data sheet**

Supplier                              TEK  
4 Howarth Court,  
Gateway Crescent,  
Chadderton, Oldham  
UK  
OL9 9XB  
0161 627 0101  
sds@jamesbriggs.co.uk

**1.4. Emergency telephone number**

**SECTION 2: HAZARDS IDENTIFICATION**

**2.1. Classification of the substance or mixture**

Classification (EC 1272/2008)                      Physical and Chemical Hazards    Flam. Aerosol 1 - H222  
Human health    EUH066; Eye Irrit. 2 - H319; STOT SE 3 - H336  
Environment    Aquatic Chronic 3 - H412  
Classification (1999/45/EEC)                      Xi; R36. F+; R12. R52/53, R66, R67.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

**2.2. Label elements**

Label In Accordance With (EC) No. 1272/2008



Signal Word                              Danger  
Hazard Statements

	H222	Extremely flammable aerosol.
	H319	Causes serious eye irritation.
	H336	May cause drowsiness or dizziness.
	H412	Harmful to aquatic life with long lasting effects.
Precautionary Statements	P102	Keep out of reach of children.
	P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
	P271	Use only outdoors or in a well-ventilated area.
	P261	Avoid breathing vapour/spray.
	P280	Wear protective clothing, gloves, eye and face protection.
	P337+313	If eye irritation persists: Get medical advice/attention.

## TEK FADE OUT THINNER 500ML

<p>P305+351+338</p> <p>P501</p> <p>Supplementary Precautionary Statements</p> <p>P211</p> <p>P251</p> <p>P273</p> <p>P264</p> <p>P304+340</p> <p>P312</p> <p>P410+412</p> <p>Supplemental label information</p> <p>EUH066</p> <p>H229</p>	<p>IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>Dispose of contents/container in accordance with local regulations.</p> <p>Do not spray on an open flame or other ignition source.</p> <p>Pressurized container: Do not pierce or burn, even after use.</p> <p>Avoid release to the environment.</p> <p>Wash contaminated skin thoroughly after handling.</p> <p>IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.</p> <p>Call a POISON CENTER or doctor/physician if you feel unwell.</p> <p>Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122° F.</p> <p>Repeated exposure may cause skin dryness or cracking.</p> <p>Pressurised container: May burst if heated</p>
---	---

### 2.3. Other hazards

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

<p>2-METHOXY-1-METHYLETHYL ACETATE <span style="float: right;">5-10%</span></p> <p>CAS-No.: 108-65-6 <span style="margin-left: 150px;">EC No.: 203-603-9</span></p>										
<table border="0" style="width: 100%;"> <tr> <td style="width: 50%;">Classification (EC 1272/2008)</td> <td style="width: 50%;">Classification (67/548/EEC)</td> </tr> <tr> <td>Flam. Liq. 3 - H226</td> <td>R10</td> </tr> </table>	Classification (EC 1272/2008)	Classification (67/548/EEC)	Flam. Liq. 3 - H226	R10						
Classification (EC 1272/2008)	Classification (67/548/EEC)									
Flam. Liq. 3 - H226	R10									
<p>ACETONE <span style="float: right;">10-30%</span></p> <p>CAS-No.: 67-64-1 <span style="margin-left: 150px;">EC No.: 200-662-2</span></p>										
<table border="0" style="width: 100%;"> <tr> <td style="width: 50%;">Classification (EC 1272/2008)</td> <td style="width: 50%;">Classification (67/548/EEC)</td> </tr> <tr> <td>Flam. Liq. 2 - H225</td> <td>F;R11</td> </tr> <tr> <td>EUH066</td> <td>Xi;R36</td> </tr> <tr> <td>Eye Irrit. 2 - H319</td> <td>R66</td> </tr> <tr> <td>STOT SE 3 - H336</td> <td>R67</td> </tr> </table>	Classification (EC 1272/2008)	Classification (67/548/EEC)	Flam. Liq. 2 - H225	F;R11	EUH066	Xi;R36	Eye Irrit. 2 - H319	R66	STOT SE 3 - H336	R67
Classification (EC 1272/2008)	Classification (67/548/EEC)									
Flam. Liq. 2 - H225	F;R11									
EUH066	Xi;R36									
Eye Irrit. 2 - H319	R66									
STOT SE 3 - H336	R67									
<p>BUTANE <span style="float: right;">10-30%</span></p> <p>CAS-No.: 106-97-8 <span style="margin-left: 150px;">EC No.: 203-448-7</span></p>										
<table border="0" style="width: 100%;"> <tr> <td style="width: 50%;">Classification (EC 1272/2008)</td> <td style="width: 50%;">Classification (67/548/EEC)</td> </tr> <tr> <td>Flam. Gas 1 - H220</td> <td>F+;R12</td> </tr> </table>	Classification (EC 1272/2008)	Classification (67/548/EEC)	Flam. Gas 1 - H220	F+;R12						
Classification (EC 1272/2008)	Classification (67/548/EEC)									
Flam. Gas 1 - H220	F+;R12									
<p>BUTYL ACETATE -norm <span style="float: right;">5-10%</span></p> <p>CAS-No.: 123-86-4 <span style="margin-left: 150px;">EC No.: 204-658-1</span></p>										
<table border="0" style="width: 100%;"> <tr> <td style="width: 50%;">Classification (EC 1272/2008)</td> <td style="width: 50%;">Classification (67/548/EEC)</td> </tr> <tr> <td>Flam. Liq. 3 - H226</td> <td>R10</td> </tr> <tr> <td>EUH066</td> <td>R66</td> </tr> <tr> <td>STOT SE 3 - H336</td> <td>R67</td> </tr> </table>	Classification (EC 1272/2008)	Classification (67/548/EEC)	Flam. Liq. 3 - H226	R10	EUH066	R66	STOT SE 3 - H336	R67		
Classification (EC 1272/2008)	Classification (67/548/EEC)									
Flam. Liq. 3 - H226	R10									
EUH066	R66									
STOT SE 3 - H336	R67									

## TEK FADE OUT THINNER 500ML

ETHYL ACETATE	5-10%
CAS-No.: 141-78-6	EC No.: 205-500-4
Classification (EC 1272/2008) Flam. Liq. 2 - H225 EUH066 Eye Irrit. 2 - H319 STOT SE 3 - H336	Classification (67/548/EEC) F;R11 Xi;R36 R66 R67
ISOBUTANE	5-10%
CAS-No.: 75-28-5	EC No.: 200-857-2
Classification (EC 1272/2008) Flam. Gas 1 - H220	Classification (67/548/EEC) F+;R12
PROPANE	10-30%
CAS-No.: 74-98-6	EC No.: 200-827-9
Classification (EC 1272/2008) Flam. Gas 1 - H220	Classification (67/548/EEC) F+;R12
SOLVENT NAPHTHA(PETROLEUM), LIGHT AROM.	5-10%
CAS-No.: 64742-95-6	EC No.:
Classification (EC 1272/2008) Flam. Liq. 3 - H226 EUH066 STOT SE 3 - H335, H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	Classification (67/548/EEC) Xn;R65. Xi;R37. N;R51/53. R10,R66,R67.
XYLENE	5-10%
CAS-No.: 1330-20-7	EC No.: 215-535-7
Classification (EC 1272/2008) Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335 STOT RE 2 - H373 Asp. Tox. 1 - H304 Aquatic Chronic 3 - H412	Classification (67/548/EEC) R10 Xn;R20/21 Xi;R38

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

### SECTION 4: FIRST AID MEASURES

#### 4.1. Description of first aid measures

General information

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

# TEK FADE OUT THINNER 500ML

## Inhalation

Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep the affected person warm and at rest. Get prompt medical attention.

## Ingestion

DO NOT INDUCE VOMITING! Rinse mouth thoroughly with water and give large amounts of milk or water to people not unconscious. Get medical attention if any discomfort continues.

## Skin contact

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

## Eye contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

### **4.2. Most important symptoms and effects, both acute and delayed**

### **4.3. Indication of any immediate medical attention and special treatment needed**

## SECTION 5: FIREFIGHTING MEASURES

### **5.1. Extinguishing media**

Extinguishing media

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

### **5.2. Special hazards arising from the substance or mixture**

Unusual Fire & Explosion Hazards

Aerosol cans may explode in a fire.

### **5.3. Advice for firefighters**

Special Fire Fighting Procedures

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### **6.1. Personal precautions, protective equipment and emergency procedures**

### **6.2. Environmental precautions**

### **6.3. Methods and material for containment and cleaning up**

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces because of explosion risk. If leakage cannot be stopped, evacuate area.

### **6.4. Reference to other sections**

## SECTION 7: HANDLING AND STORAGE

### **7.1. Precautions for safe handling**

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

### **7.2. Conditions for safe storage, including any incompatibilities**

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

### **7.3. Specific end use(s)**

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### **8.1. Control parameters**

## TEK FADE OUT THINNER 500ML

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
2-METHOXY-1-METHYLETHYL ACETATE	WEL	50 ppm(Sk)	274 mg/m3(Sk)	100 ppm(Sk)	548 mg/m3(Sk)	
ACETONE	WEL	500 ppm	1210 mg/m3	1500 ppm	3620 mg/m3	
BUTANE	WEL	600 ppm	1450 mg/m3	750 ppm	1810 mg/m3	
BUTYL ACETATE -norm	WEL	150 ppm	724 mg/m3	200 ppm	966 mg/m3	
ETHYL ACETATE	WEL	200		400		
PROPANE		Asphyxiating	Asphyxiating.	Asphyxiating	Asphyxiating.	
XYLENE	WEL	50 ppm(Sk)	220 mg/m3(Sk)	100 ppm(Sk)	441 mg/m3(Sk)	

WEL = Workplace Exposure Limit.

### 8.2. Exposure controls

Protective equipment



Engineering measures

Provide adequate general and local exhaust ventilation.

Respiratory equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. Use chemical cartridge protection with appropriate cartridge.

Hand protection

Use protective gloves.

Eye protection

Use approved safety goggles or face shield.

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Typical
Odour	Characteristic.
Flammability Limit - Lower(%)	0.8
Flammability Limit - Upper(%)	9.0

### 9.2. Other information

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

### 10.2. Chemical stability

Stable under normal temperature conditions.

### 10.3. Possibility of hazardous reactions

### 10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

# TEK FADE OUT THINNER 500ML

## 10.5. Incompatible materials

## 10.6. Hazardous decomposition products

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

#### Inhalation

May cause irritation to the respiratory system. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system. Irritating to respiratory system.

#### Ingestion

May cause discomfort if swallowed. May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach.

#### Skin contact

Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent on skin. May cause cracking of skin, and eczema. May cause allergic contact eczema. May cause sensitisation by skin contact. Irritating to skin.

#### Eye contact

Irritating to eyes. May cause chemical eye burns.

#### Route of entry

Inhalation. Skin and/or eye contact.

## SECTION 12: ECOLOGICAL INFORMATION

#### Ecotoxicity

Dangerous for the environment if discharged into watercourses.

### 12.1. Toxicity

### 12.2. Persistence and degradability

### 12.3. Bioaccumulative potential

### 12.4. Mobility in soil

### 12.5. Results of PBT and vPvB assessment

### 12.6. Other adverse effects

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

## SECTION 14: TRANSPORT INFORMATION

### 14.1. UN number

UN No. (ADR/RID/ADN)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950

### 14.2. UN proper shipping name

Proper Shipping Name                      AEROSOLS

### 14.3. Transport hazard class(es)

# TEK FADE OUT THINNER 500ML

ADR/RID/ADN Class	2
ADR/RID/ADN Class	Class 2: Gases
ADR Label No.	2.1
IMDG Class	2.1
ICAO Class/Division	2.1
Transport Labels	



## **14.4. Packing group**

ADR/RID/ADN Packing group	Not Applicable
IMDG Packing group	Not Applicable
ICAO Packing group	Not Applicable

## **14.5. Environmental hazards**

Environmentally Hazardous Substance/Marine Pollutant  
No.

## **14.6. Special precautions for user**

EMS F-D, S-U

## **14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

## **SECTION 15: REGULATORY INFORMATION**

### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Uk Regulatory References

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002.

The Control of Substances Hazardous to Health Regulations 2002.

Statutory Instruments

The Control of Substances Hazardous to Health Regulations 2002.

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002.

Approved Code Of Practice

Classification and Labelling of Substances and Preparations Dangerous for Supply.

Guidance Notes

Workplace Exposure Limits EH40.

Introduction to Local Exhaust Ventilation HS(G)37.

CHIP for everyone HSG(108).

### **15.2. Chemical Safety Assessment**

## **SECTION 16: OTHER INFORMATION**

Revision Date	12/04/2016
Revision	2
Supersedes date	08/04/2016

## TEK FADE OUT THINNER 500ML

### Risk Phrases In Full

R12	Extremely flammable.
R10	Flammable.
R20/21	Harmful by inhalation and in contact with skin.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R11	Highly flammable
R36	Irritating to eyes.
R37	Irritating to respiratory system.
R38	Irritating to skin.
R66	Repeated exposure may cause skin dryness or cracking.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R67	Vapours may cause drowsiness and dizziness.

### Hazard Statements In Full

H319	Causes serious eye irritation.
H315	Causes skin irritation.
H222	Extremely flammable aerosol.
H220	Extremely flammable gas.
H226	Flammable liquid and vapour.
H332	Harmful if inhaled.
H312	Harmful in contact with skin.
H412	Harmful to aquatic life with long lasting effects.
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs <<Organs>> through prolonged or repeated exposure.
H336	May cause drowsiness or dizziness.
H335	May cause respiratory irritation.
EUH066	Repeated exposure may cause skin dryness or cracking.
H411	Toxic to aquatic life with long lasting effects.